

8000XHT Series Flow Meters

MODEL NUMBER	FLOW RANGE	FITTING TYPE	CONNECTION SIZE	MEASUREMENT	PRICE
08006XHTSA2	0.95 - 9.5 LPM / 0.25 - 2.5 GPM	SAE Fittings	9/16-18 SAE	Flow	\$640.00
08006XHTSA2-T	0.95 - 9.5 LPM / 0.25 - 2.5 GPM	SAE Fittings	9/16-18 SAE	Flow & Temperature	\$820.00
08006XHTSA4	1.1 - 17 LPM / 0.3 - 4.5 GPM	SAE Fittings	9/16-18 SAE	Flow	\$640.00
08006XHTSA4-T	1.1 - 17 LPM / 0.3 - 4.5 GPM	SAE Fittings	9/16-18 SAE	Flow & Temperature	\$820.00
08008XHTSA6	1.5 - 23 LPM / 0.4 - 6.0 GPM	SAE Fittings	3/4-16 SAE	Flow	\$640.00
08008XHTSA6-T	1.5 - 23 LPM / 0.4 - 6.0 GPM	SAE Fittings	3/4-16 SAE	Flow & Temperature	\$820.00
08008XHTSA10	3.0 - 38 LPM / 0.8 - 10 GPM	SAE Fittings	3/4-16 SAE	Flow	\$640.00
08008XHTSA10-T	3.0 - 38 LPM / 0.8 - 10 GPM	SAE Fittings	3/4-16 SAE	Flow & Temperature	\$820.00
08012XHTSA16	4.5 - 60 LPM / 1.2 - 16 GPM	SAE Fittings	1 1/16-12 SAE	Flow	\$705.00
08012XHTSA16-T	4.5 - 60 LPM / 1.2 - 16 GPM	SAE Fittings	1 1/16-12 SAE	Flow & Temperature	\$885.00

NOTE



Standard 8000XHT Series flow meters are calibrated with water at approximately 25 °C / 77 °F. The use of fluids other than water may affect the accuracy of measurement due to differences in viscosity.

Proteus' world-class calibration capability allows us to deliver instruments with specialized fluid- and temperature-specific calibrations to ensure accuracy in your most critical processes. Please contact Applications Support at tech@proteusind.com or (650) 964-4163 for more information.

Optional Components

PART NUMBER	DESCRIPTION	PRICE
G110529	M12 cable for 8000XHT Series flow meters (straight female • 8-pin • 24 AWG • length: 2.0 m / 6.6 ft)	\$95.00

How to Order

- » Phone (650) 964-4163
- » Fax (650) 965-0304
- » E-mail sales@proteusind.com

Note: A purchase order is required for all non-credit card orders.