



WeldSaver™

Product Configuration Form

Product Series	 WeldSaver 5 No keypad or display	 WeldSaver 6 Local keypad with display	Both product series offer the same functional capabilities and performance characteristics, with vortex flow sensors and an upper flow limit of 50 LPM / 13 GPM.	
OR				
SELECT OPTIONS BELOW				
Network Interface	EtherNet/IP™	PROFINET®		
	Other (please specify):			
Number of Network Ports	Single	Dual		
Default IP Address	172.24.1.1	Other (please specify):		
Firmware/Bitmap Version	Standard	Other (please specify):		
Water Fittings	BSPG (G) 3/4" female	NPT 3/4" female	NPT 3/4" male	
Shutoff Valve	Electric solenoid valve	Pneumatic angle seat valve	None – M12 connector only	
	None – cable only (please specify connector):			
Temperature Measurement	Yes	No		
Units of Measure	LPM / °C	GPM / °F		
Flow Parameters	Default Value	Custom Value (please specify)		
Flow Warning	11.4 LPM / 3.0 GPM			
Flow Fault	7.6 LPM / 2.0 GPM			
Slow Leak Difference	3.8 LPM / 1.0 GPM			
Slow Leak Delay	4000 msec			
Stabilization Delay	4 sec	1 sec	2 sec	6 sec 8 sec
Leak Response Sensitivity	Normal	Slowest	Slow	Fast Fastest
Other Requirements/Requests				
Quantity to be Quoted	1	Other (please specify):		

NAME: _____ TITLE: _____
 EMAIL: _____ DIVISION: _____
 PHONE: _____ COMPANY: _____

Please send this completed form to WeldSaver Applications Support at weldsaver@proteusind.com.



Proteus Industries Inc.
 340 Pioneer Way, Mountain View, CA 94041
 Tel: (650) 964-4163 Fax: (650) 965-0304
www.proteusind.com sales@proteusind.com

Information in this document was correct at the time of printing; however, specifications are subject to change as Proteus Industries' continuous improvement processes establish new capabilities.

© Proteus Industries Inc. All rights reserved. All other company and product names may be trademarks of their respective companies.

MKT00127 Rev 002 06/2020