

Product Configuration Form

Product Series	WeldSaver 5 No keypad or display	WeldSaver 6	Local keypad with display	Contant	6 with eVac™ Coolant Retraction Module
SELECT OPTIONS BELOW					
Network Interface	EtherNet/IP™	PROFINET ®			
	Other (please specify):				
Number of Network Ports	Single	Dual			
Default IP Address	172.24.1.1	Other (please specify):			
Firmware/Bitmap Version	Standard	Other (please specify):			
Water Fittings	BSPP (G) 3/4" female	NPT 3/4" female NPT 3/4" male			
Shutoff Valve	Electric solenoid valve	Pneumatic angle seat valve			
	Coolant Retraction Module (WeldSaver 6 with eVac only) None – M12 co			connector only	
	None – cable only (please specify connector):				
Temperature Measurement	Yes No				
Units of Measure	LPM / °C GPM / °F				
Flow Parameters	Default Value	efault Value Custom Value (please specify)			
Flow Warning	11.4 LPM / 3.0 GPM				
Flow Fault	7.6 LPM / 2.0 GPM	7.6 LPM / 2.0 GPM			
Slow Leak Difference	3.8 LPM / 1.0 GPM				
Slow Leak Delay	4000 msec				
Stabilization Delay	4 sec	1 sec	2 sec	6 sec	8 sec
Leak Response Sensitivity	Normal	Slowest	Slow	Fast	Fastest
Other Requirements/Requests					
Quantity to be Quoted	1 Other (please specify):				

NAME:	TITLE:
EMAIL:	DIVISION:
PHONE:	COMPANY:

Please send this completed form to WeldSaver Applications Support at weldsaver@proteusind.com.



Proteus Industries Inc. 340 Pioneer Way, Mountain View, CA 94041 Tel: (650) 964-4163 Fax: (650) 965-0304 www.proteusind.com sales@proteusind.com

Information in this document was correct at the time of printing; however, specifications are subject to change as Proteus Industries' continuous improvement processes establish new capabilities. © Proteus Industries Inc. All rights reserved. All other company and product names may be trademarks of their respective companies. MKT00127 Rev 004 08/2023