

Product Selection Guide

Product Series	WeldSaver 5 No keypad or display	WeldSaver 6	Local keypad with display	same function performance of with vortex flo	series offer the Ial capabilities and characteristics, w sensors and limit of 50 LPM /	
	SELECT OP	TIONS BELOW				
Network Interface	EtherNet/IP™	PROFINET®				
	Other (please specify):					
Number of Network Ports	Single Dual					
Default IP Address	172.24.1.1 Other (please specify):					
Firmware/Bitmap Version	Standard Other (please specify):					
Water Fittings	BSPP (G) 3/4" female	NPT 3/4" fem	NPT 3/4" female		NPT 3/4" male	
Shutoff Valve	Electric solenoid valve	Pneumatic angle seat valve		None – M12 connector only		
	None – cable only (please specify connector):					
Temperature Measurement	Yes No					
Units of Measure	LPM / °C GPM / °F					
Flow Parameters	Default Value Custom Value (please specify)					
Flow Warning	11.4 LPM / 3.0 GPM					
Flow Fault	7.6 LPM / 2.0 GPM					
Slow Leak Difference	3.8 LPM / 1.0 GPM					
Slow Leak Delay	4000 msec					
Stabilization Delay	4 sec	1 sec	2 sec	6 sec	8 sec	
Leak Response Sensitivity	Normal	Slowest	Slow	Fast	Fastest	
Other Requirements/Requests						
Quantity to be Quoted	1 Other (please specify):					

NAME:	TITLE:
EMAIL:	DIVISION:
PHONE:	COMPANY:

Please send this completed form to WeldSaver Applications Support at weldsaver@proteusind.com.



Proteus Industries Inc. 340 Pioneer Way, Mountain View, CA 94041 Tel: (650) 964-4163 Fax: (650) 965-0304 www.proteusind.com sales@proteusind.com

Information in this document was correct at the time of printing; however, specifications are subject to change as Proteus Industries' continuous improvement processes establish new capabilities. © Proteus Industries Inc. All rights reserved. All other company and product names may be trademarks of their respective companies. MKT00127 Rev 001 02/2020